



**Unloads dry bulk materials from both trucks and rail cars**

The Lift-Mate<sup>™</sup> Series 703 truck and rail car connector is specially designed to contain dry bulk solid materials when discharging from hopper bottom rail cars or trucks. The Lift-Mate is easy to use and creates a dust-tight connection between the outlet of a hopper bottom rail car and/or truck for cleaner and faster unloading and discharging. It comes complete with an outlet flange aligner control for exact positioning of the Lift-Mate connector. This makes it simple and quick to use when trying to align to meet the outlet of the rail car or truck.

The lifting mechanism is powered by a heavy-duty hydraulic cylinder, which uses an air-over-oil combination for a smooth and safe position control. The rugged hydraulic cylinder has an oversized piston rod for additional strength and to provide more than adequate power for lifting and sealing. The mating connection to the truck or rail car has a replaceable, extra wide seal to provide longer life, even under severe operating conditions.

*Dynamic Air Conveying Systems is a registered trademark and Lift-Mate is a trademark of Dynamic Air Inc., St. Paul, MN.*

Manual air control valves and oil reservoir tank are fully assembled and ready for easy floor mounting. The controls include a special lockout for security and safety purposes. The overall simplicity of the Lift-Mate connector makes maintenance easy, because the air-over-oil power source only requires standard available compressed air for operation.

**Features**

- Built-in aligner
- Safety lockout panel
- Rugged rubber seal
- Installs quickly
- Preassembled
- Explosion proof
- 2500 lbs. of sealing force
- Oversized lifting rod
- Nylon powder coated

**Benefits**

- Stainless steel or aluminum construction
- Position sensors
- Custom adapters for trucks and rail cars

Bulletin 21127-T  
© 2011 Dynamic Air Inc.